



CASING TUBES

TECHNICAL SPECIFICATIONS

TYPE SIZE	ROD O.D. (mm)	ROD I.D. (mm)	COUPLING I.D. (mm)	THREADS PER INCH (T.P.I.)
METRIC				
146 (143/134)	143.3	133.3	-	4
131 (128/119)	128.4	118.4	-	4
116 (113/104)	113.4	103.4	-	4
101 (98/89)	98.4	88.4	-	4
86 (84/77)	84.4	77.5	-	4
76 (74/67)	74.4	67.5	-	4
66 (64/57)	64.4	57.5	-	4
56 (54/47)	54.3	47.4	-	4
46 (44/37)	44.3	37.4	-	4
DCDMA-BS ["W" series]				
SW	168.5	154.0	-	3
PW	140.0	125.0	-	3
HW	114.3	101.6	-	4
NW	89.1	76.4	-	4
BW	73.1	60.4	-	4
AW	57.3	48.5	-	4
DCDMA-BS ["X" series]				
PX	140.0		125.0	5
HX	114.5		100.1	5
NX	89.0		76.4	8
BX	73.1		60.4	8
AX	57,3		48.5	8
HEAVY DUTY				
HD 140/125	140.0	125.0	-	4
HD 127/111	127.0	111.0	-	4
HD 117/104	117.0	104.0	-	4

The standard effective lengths are 3.0, 1.5, 1.0 & 0.5 meters. Other lengths may be manufactured upon request.

All casing tubes have right hand threads. Left hand threads can be manufactured if requested.

ABBREVIATIONS

O.D.: Outer diameter, I.D.: Inner diameter, HD: Heavy Duty

Technodrill constantly improves its products and therefore reserves the right to modify and change specifications without prior notice.